



Nominal Washer Size		INTERNAL-EXTERNAL TOOTH LOCK WASHERS						ASME B18.21.1 2009
		A		B		C		
		Inside Diameter		Outside Diameter *		Thickness		
		Max	Min	Max	Min	Max	Min	
4	0.112	0.123	0.115	0.475	0.460	0.021	0.016	
6	0.138	0.150	0.141	0.510	0.495	0.028	0.023	
8**	0.164	0.176	0.168	0.506	0.494	0.028	0.023	
8	0.164	0.176	0.168	0.610	0.580	0.034	0.028	
10	0.190	0.204	0.195	0.610	0.580	0.034	0.028	
1/4	0.250	0.267	0.256	0.760	0.725	0.040	0.032	
5/16	0.312	0.332	0.320	0.900	0.865	0.040	0.032	
3/8	0.375	0.398	0.384	0.985	0.965	0.045	0.037	
7/16	0.438	0.464	0.448	1.070	1.045	0.050	0.042	
1/2	0.500	0.530	0.512	1.260	1.220	0.055	0.047	
5/8	0.625	0.663	0.640	1.410	1.380	0.060	0.052	

*Industry standards allow for washers with larger outside diameter dimensions.

**ITW Shakeproof specification, not ASME B18.21.1

Description	A circular washer with twisted prongs or teeth protruding from both the inside and outer edges of the washer.	
Applications/Advantages	Preferred lockwasher in the following situations: (1) where a larger bearing surface is desired; (2) for an optimum electrical connection; (3) where the hole is oversized or out of round; (4) as an insert between two adjustable pieces where a longitudinal or rotational adjustment must be maintained.	
Material	Steel	Stainless
	SAE 1050 - 1065 or equivalent spring steel	301 - 305 stainless steel
Hardness	Rockwell C40 - 50	Annealed: Rockwell B88 minimum 1/4 hard thru full hard: Rockwell C 20 - 45
Plating	See Appendix-A for information about the plating of steel lock washers.	Stainless lockwashers are usually supplied plain or with a black oxide conversion finish.