


# Weld Nuts

# Offset Hole

# Single Projection



**WELD NUTS - OFFSET HOLE DESIGN WITH SINGLE PROJECTION**

Paulin®

Size	A	C	B	F	E	G	D	K	Sheet Hole
	Width	Thickness	Length	Pilot Diameter	Pilot Height	Projection Width	Projection Height	Center of Pilot Hole to Outside of Rounded Edge	
6-32	.453	.098	.640	.198	.042	.193	.014	.202	.203
	.433	.088	.610	.178	.026	.183	.010	.172	
8-32	.453	.098	.640	.213	.042	.193	.014	.202	.219
	.433	.088	.610	.193	.026	.183	.010	.172	
10-24	.453	.098	.640	.244	.042	.193	.014	.202	.250
	.433	.088	.610	.224	.026	.183	.010	.172	
10-32	.453	.098	.640	.244	.042	.193	.014	.202	.250
	.433	.088	.610	.224	.026	.183	.010	.172	
1/4-20	.520	.130	.827	.307	.062	.224	.025	.265	.312
	.495	.120	.797	.287	.046	.214	.021	.235	
1/4-28	.520	.130	.827	.307	.062	.224	.025	.265	.312
	.495	.120	.797	.287	.046	.214	.021	.235	
5/16-18	.655	.145	.999	.369	.092	.317	.029	.296	.375
	.620	.135	.969	.349	.076	.307	.025	.266	
3/8-16	.655	.145	1.140	.448	.102	.317	.029	.359	.453
	.620	.135	1.110	.428	.086	.307	.025	.329	
3/8-24	.655	.145	1.140	.448	.102	.317	.029	.359	.453
	.620	.135	1.110	.428	.086	.307	.025	.329	

<b>Description</b>	A four-sided, internally threaded fastener with rounded edges at the two ends most opposite each other. The threaded hole is set off to one side and has a pilot for the entire circumference of the opening which extends above the flat surface of the nut. The remainder of the top surface of the nut is flat.
<b>Applications/Advantages</b>	This style weld nut is to be used with thinner gage metals to reinforce an area. The tab allows the installer to use multiple sizes of electrodes, thus improving efficiency by reducing equipment changes. The height of the pilot minimizes the amount of welding residue that could clog the threads.
<b>Material</b>	1006 - 1010 Low Carbon Steel

®Paulin is a registered trademark of H. Paulin & Company Limited.